

# Dexion Dynamic Locking Range - Silver Level



DCK



DCR



SOLA

## Product overview

The Dexion Dynamic Locking Range offers users three distinct levels of locking, each with varying connectivity, security and functionality options. Silver level locking offers key-pad and RFID operated locks supported by battery power.

These user friendly keyless locking solutions are reliable, simple to use and provide enhanced lock management via Assigned or Shared use functionality, and electronic Managers keys. Locks can be Assigned to a user for an extended period, or be programmed for Shared use so a user simply chooses any available storage unit and enters their own temporary code for interim use. Optional electronic key functionality introduces a programming key and an optional manager bypass key. The programming and manager bypass keys make programming fast and effective relative to using programming with the keypad. Electronic keys allow lock reprogramming, code / user credential re-set, audit inspection and external power in case of battery failure.

Our Silver level locking options have a slick body style made with a durable metal housing. They incorporate a turn handle, have visual and audible indicators, and a 3-5 year battery life. All Silver level locks offer an Accessibility User Key which is compliant with ADA guidelines (Americans with Disabilities Act).

The 'SOLA' lock suits all applications and budgets. Its simple keypad interface and low profile turn handle provide security and versatility. The 'DCK' lock has a key pad user interface and a four digit user code while the 'DCR' lock uses a Radio Frequency Identification (RFID) user interface. This 'DCR' RFID lock is based on the MiFare technology platform and can be operated by either a RFID card or an RFID Fob key. In the event that existing staff RFID cards are not compatible with the lock, a low profile Mifare RFID sticker can easily be added to existing staff cards for lock operation.

The Silver level locking can be fitted to Dexion's Strata 2 Tambour Door Cabinets and the Dexion Agile Locker Range. They can also be used in place of traditional aisle locks, or the main unit lock on Dexion's Freetrack 2 / Mekdrive 2 / Multibay 2 Compactus, either during installation or at a later stage.

## Product applications

Strata 2 Tambours	DigiLock DCK
	Digilock DCR
	Digilock SOLA
Agile Locker Range	DigiLock DCK
	Digilock DCR
	Digilock SOLA
Freetrack 2 Manual Compactus	DigiLock DCK
	Digilock DCR
	Digilock SOLA
Freetrack 2 MekDrive 2 Compactus	DigiLock DCK
	Digilock DCR
	Digilock SOLA
MultiBay2 Compactus	DigiLock DCK
	Digilock DCR
	Digilock SOLA

## Technical specifications

### Digilock DCK

- Keypad operation Cam locking.
- Assigned or shared use functionality.
- Recess mount with knob or with American's Disabilities Act (ADA) compliant lever.
- Operates with user selected 4-digit code and handle rotation.
- Tamper guard.
- Optional electronic key functionality includes a programming key and optional manager bypass keys.
- Visual and audible usage indicators.
- Powered by 3 premium AA batteries.
- 3-5 year battery life.
- Low battery and binding indicator.
- Two year product warranty.



DCK

### Digilock DCR

- RFID operation.
- Cam locking.
- Assigned and Shared use functionality.
- Recess mount with knob or with American's Disabilities Act (ADA) compliant lever.
- ADA compliant lever.
- Operates with any RFID access card and handle rotation.
- Tamper guard.
- Optional electronic key functionality includes a programming key and optional manager bypass keys.
- Visual and audible usage indicators.
- Powered by three premium AA batteries.
- 3-5 year battery life.
- Low battery and binding indicator.
- Two year product warranty.
- Compatible RFID standards:  
ISO 14443A  
ISO 14443B  
ISO 15693

\*Shown with ADA compliant lever



DCR\*

### Digilock SOLA

- IP55 rated.
- Keypad operation.
- Cam locking - offset and flat cam included.
- 90 degree cam rotation to top, bottom, left or right.
- Shared and assigned use functionality.
- Surface mount vertical body.
- Accommodates door thickness of 0.25 - 22.22mm.
- Operates with 4-digit user code and lever rotation.
- Optional electronic key functionality includes a programming key and optional manager bypass keys with external power.
- ADA Accessibility User Key.
- Visual and audible feedback.
- Powered by two AAA batteries.
- External access for battery replacement.
- Low battery indicator.
- Two year product warranty.



SOLA