

Dexion Freetrack 2 Compactus - Dynamic Locking



compactus[®]

Product overview

The Dexion Freetrack 2 Compactus secured with Dexion Dynamic Locking revolutionises light weight storage solutions. The system offers the most comprehensive security and access accountability options in the market with three distinct levels of locking to choose from, each with varying connectivity, security and functionality options. Dexion Freetrack 2 Compactus are secured as standard with our Bronze level latch locks. The Silver level locking introduces keypad and RFID card operated locks supported by battery power Gold level locking utilises RFID card or even app operated locking for the user, with centralised server connectivity for administrators. The Gold level locking is available with live connection to your BAC system (Building Access Control) and / or Microsoft Active Directory system, and is commonly employed in ABW (Activity Based Workplace) environments.

The Gold level lock with its centralised server for administrators can be applied to a range of other Dexion products to deliver a seamless and dynamic locking system to all the storage mediums in your fitout for ultimate access accountability to stored contents. Other products include Dexion's Mekdrive 2 Compactus, Multibay Compactus and Strata 2 Tambour Door Cabinets.

Dexion's Freetrack 2 systems do not require floor fixing so are easier and far more cost effective to install, relocate or reconfigure than standard fixed track systems. The lighter weight of the system reduces the chance of operator strain and loads imposed on the floor. Easily upgrade from Ultima CI-80 static shelving to any Freetrack system.

Key features and benefits

- Robust aluminium anodised track components provides strength and a streamline finish that constitutes to a modern attractive appearance.
- Design the perfect solution with unlimited base lengths.
- A lighter weight system reduces operator strain and loads imposed on the floor.
- Tracks do not require fixing eliminating any damage to floor coverings.
- Track and runner combinations add only 65mm to the overall shelving height.
- Dynamic locking options with varying levels of connectivity, security and functionality.

Note: Refer to the Dexion Dynamic Locking Range specification sheets (Gold, Silver, Bronze) for more detail on the lock functions and suitable applications.

Technical specification

Drive type	Manual
Shelving & accessory system	Ultima CI-80
Maximum system width	1800mm
Shelving width (bay width)	750mm 900mm 1050mm 1200mm
Shelving depth	250mm 300mm 400mm 450mm 500mm 600mm
Shelving height	1875mm 2175mm 2400mm
Overall system height	1940mm 2240mm 2465mm
Maximum bay carrying capacity*	500kg
Maximum movable block load*	1000kg
Standard colour	Stone White
Other colours	Refer to Colour Selector

*Uniformly distributed load. Shelf, beam and bay capacities may vary. Please contact the Dexion sales support team for specific maximum loads based on your configuration.

Dynamic locking levels

Gold	TZ SwingHandle - TZ Enabled™ TZ SlideHandle™
Silver	Digilock DCK (Key Pad) Digilock DCR (RFID) Digilock SOLA (Key Pad)
Bronze	Latch Lock (Padlock) CAM Lock (Key) TZ SwingHandle - TZ Ready™

Compatible locks

The Dexion Dynamic Locking Range offers users three distinct levels of locking, each with varying connectivity, security and functionality options. Please reference the Dexion Dynamic Locking (Gold, Silver and Bronze) specification sheets for more information.

Lock types

Gold: TZ Locking Solutions
 TZ SwingHandle - TZ Enabled™
 TZ SlideHandle™



TZ SlideHandle™



TZ SwingHandle™

Silver: Digilock Solutions
 Digilock DCK
 Digilock DCR
 Digilock SOLA



DCK



DCR*



SOLA

*shown with ADA compliant lever

Bronze:
 Latch Lock (Padlock)
 CAM Lock (Key)
 TZ SwingHandle - TZ Ready™



Latch Lock



Cam Key Lock



TZ SwingHandle - TZ Ready™